

JBC CDB

Soldering

JBC


[Product Application Map](#)
[News](#)


For general electronics application.

It Includes JBC Most Efficient Soldering System offering the best quality and extending tip life up to 5 times.

- Complete Tip Cleaning System, with exclusive fast and safe Cartridge Exchanger.

- Connectivity:
 - Fume Extractor
 - Datas Download
 - Software Updates
 - Traceability

- T245 General Purpose Handle working with C245 Cartridges



Don't believe us...
TRY IT!



REFERENCES

CD-1BQF 120 V

CD-2BQF 230 V

CD-9BQF 100 V

PRODUCT COMPOSITION

- 1 CD Control Unit
- 1 T245 General Purpose Handle (cartridge not included)

SPECIFICATIONS

Selectable Temperature	90 to 450 °C / 190 to 840 °F
Peak power	130 W - 23.5 V
ESD safe	Meet ANSI/ESD S20.20-2021
Tip to ground resistance	<2 ohms
Tip to ground voltage	<2 mV RMS

CONNECTIVITY

USB-B	Software PC / Firmware update
FAE Connector	FAE Fume Extractor control

DIMENSIONS AND WEIGHT

Control Unit	170 x 176 x 145 mm / 2.74 kg. 6.69 x 6.93 x 5.71 in / 6.04 lb.
Package	234 x 234 x 258 mm / 3.34 kg. 9.21 x 9.21 x 10.16 in / 7.36 lb.

CONNECTABLES

Compatible tools



T210-A

Precision Handle



T210-PA

Blue Grip Precision Handle



T245-A

General Purpose Handle



T245-GA

General Purpose Handle with reinforced cable



T245-PA

Blue Grip General Purpose Handle

Accessories



0012994

Tool Holder for CDB & CDS



CC1001

Cable Collector



FAE2-5B

Fume Extractor for 2 Workbenches



FAE1

Fume Extractor for 1 Workbench